

C-PANEL / 01

Concretta Concrete Panel

Technical Information

What is C-Panel?

Panels manufactured from pure cement, quartz and organic materials. As a cement-based product, it is 100% odorless and poses no health risk. Due to its raw material composition, it is naturally Class A non-combustible. The primary installation method is adhesive bonding; screws may also be used for additional support. It is easy to process and cut with standard carpentry tools. Its special self-protective surface prevents concrete dust.



Easy Installation

In addition to its visual impact and refined appearance, C-Panel is quick and easy to install using readily available adhesives and fixings. This helps reduce construction time, allows customers to install the panels themselves, and lowers labour costs on large-scale projects.

Panel Dimensions

Ready-to-use concrete panel...

Standard products: 60 cm x 120 cm.

Thickness: 7-11 mm (+/-10%);
weight: 8-15 kg/m².

Custom sizes are available.

Colouring is available.

Applications...

Interior and exterior facades.

C-PANEL / 02

Concretta Concrete Panel

Technical Specification

- 01** 8-11 mm panels shall be used.
- 02** The panels shall be resistant to scratching and to interior and exterior weather conditions.
- 03** The panels shall be suitable for use in wet areas.
- 04** The panels shall be water-resistant and slip-resistant.
- 05** The panels shall be suitable for use on walls, floors and furniture surfaces.
- 06** Cleaning and maintenance shall not require professional equipment; routine maintenance shall be easy.
- 07** The final decorative layer shall be a cement-based finish with durable performance properties.
- 08** The product shall not be paint-based.
- 09** Powder pigments may be added to achieve colour harmony in grey tones.
- 10** Installation shall be carried out by adhesive bonding or, where required, by screw fixing.

